

BISCO[®] 7430 – Firm Flame Resistant Sponge Silicone – Data Sheet

BISCO[®] 7430 is a closed-cell silicone sponge sheet material designed for flame resistant applications. It is a firm grade available in sheets.

Features and Benefits

- Flame resistant
- Handles temperature extremes
- Excellent gasket material
- UV / Ozone resistant

Specifications

- BMS 1-60 Type 1, Gr. C

BISCO 7430		
Property	Test Method	Typical Value
<i>PHYSICAL</i>		
Color		Gray
Density, lb./ft ³	ASTM D 1056	35
Compression Force Deflection, psi	Force measured @ 25% Deflection ASTM D 1056	14 – 22psi (Firm stiffness)
Compression Set, % max.	ASTM D 1056 Test D @ 212°F (100°C), 22 hrs.	35%
Tensile Strength, psi	ASTM D 412	200
Elongation, %	ASTM D 412	250
Water Absorption, %	ASTM D 1056	5% max
<i>FLAMMABILITY</i>		
Flame Resistance	FMVSS302	Pass
Temperature Resistance		-85°F to +400°F

Notes:

1. Additional technical information is available.
2. Typical values are a representation of an average value for the population of the property. For specification values contact Rogers Corporation.



The information contained in this Data Sheet is intended to assist you in designing with Rogers' BISCO Silicone Materials. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown on the Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers' BISCO Silicone Materials for each application. The Rogers logo, BISCO logo, Helping power, protect, connect our world and BISCO are trademarks of Rogers Corporation or one of its subsidiaries. © 2009, 2016, 2018, 2019 Rogers Corporation, All rights reserved. Printed in U.S.A., 0119-PDF, Publication #180-168