




Arlon Silicones Technology

1100 Governor Lea Road, Bear, DE 19701
1.302.834.2100 • 1.302.834.4021 (Fax)

PRODUCT INFORMATION SHEET	
LW201Xxx-P0	

PRODUCT INFORMATION		
Design / Construction	Value	Tolerance
Design / Construction	Triangular Cross Section Fusible Tape	
Product Thickness, Inches	.020	±.003
Overall Thickness, Inches	.020	±.003
Dielectric Strength, Volts/mil	N/A	N/A
Government Bond, lb/in	N/A	N/A
Volume Resistivity, Ohm-cm	N/A	N/A
Water Absorption, %	N/A	N/A
Overall Width, Inches	1.0	±1/16
Interleave	Poly	
Product Color	Gray	
Product Shelf Life	12 months from date of manufacture @75°F	
	<i>Note: Shelf life is defined as the duration of time for which the product will meet the physical requirements outlined below. It does not guarantee the product's usefulness in all applications.</i>	
Recommended Cure Cycle	N/A	
Recommended Postcure Cycle	N/A	
Product Operating Temperature	-60°F to 400°F	
FLAME RETARDANCE INFORMATION		
UL Recognition	N/A	
Flame Test Method	N/A	
Flame Test Information	Value	Tolerance
Flame Time, seconds	N/A	
Glow Time, seconds	N/A	
Char Length, inches	N/A	
COMPOUND INFORMATION		
Physical Property	Value	Tolerance
Tensile Strength, psi	700	Minimum
Elongation, %	300	Minimum
Tear Strength, lb/in	N/A	N/A
Compression Set, %	N/A	N/A
Thermal Conductivity, W/m•K	N/A	N/A
Durometer, Shore A Points	N/A	N/A
SUBSTRATE INFORMATION		
Substrate Type	N/A	
Physical Property	Value	Tolerance
Thickness, in	N/A	N/A
Uncoated Fabric Break Strength, lb/in		
Warp Direction:	N/A	N/A
Fill Direction:	N/A	N/A

The data presented in this document represents typical values for the production material.
This data should not be used to write, or in place of, material specifications.