



# PRODUCT SAFETY INFORMATION SHEET

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

TRADE NAME:	RO1200™ Laminates Series
CHEMICAL FAMILY:	Polytetrafluoroethylene Composite
USE OF ARTICLE	Printed Circuit Boards
DATE ISSUED:	September 3, 2020
COMPANY/UNDERTAKING IDENTIFICATION:	Rogers Corporation 1100 Governor Lea Rd Bear, DE 19701 Phone: 001-800-635-9333 Fax: 001-302-834-2940 Email: msdsinfo@rogerscorporation.com

## 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE MATERIAL:	NE
LABELING REQUIREMENTS:	NE
EFFECTS OF OVEREXPOSURE:	None are expected with normal handling. Cutting and other finishing operations may create dust. Ventilation and personnel protection should be similar to all operations generating nuisance dust. Processing material at temperatures exceeding decomposition temperature may release toxic fumes.
INHALATION:	Dust may cause respiratory irritation. Remove to fresh air and seek medical attention if necessary. Exposure to copper fume or PTFE decomposition products may cause symptoms of metal or Polymer Fume Fever. This is characterized by flu like symptoms (fever, chills, muscle aches) that last 24 hours.
EYE CONTACT:	Dust may cause irritation. Flush eyes with water and seek medical attention if necessary.
SKIN CONTACT:	Dust may cause irritation. Wash thoroughly with soap and water.
INGESTION:	None known.
CHRONIC:	NE

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is produced as an “article” as defined in 20 CFR 1910.1200 and REGULATION (EC) N° 1907/2006 is therefore exempt from the Hazard Communication Standard and REACH. Since this material does not release and will not result in exposure to a hazardous chemical under normal conditions of use, no Safety Data Sheet is required.

<u>Chemical Name</u>	<u>CAS No.</u>	<u>EINECS /ELINCS</u>	<u>%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Polytetrafluoroethylene	9002-84-0	204-126-9	Varies	NE	NE
Fiberglass	65997-17-3	266-046-0	Varies	5 mg/m <sup>3</sup> (Resp. Dust)	1 f/cc (Resp. Fibers)
Amorphous Silica	60676-86-0	262-373-8	Varies	5 mg/m <sup>3</sup> (Resp. Dust)	3 mg/m <sup>3</sup> (Resp. Dust)
Ceramic Filler (Nuisance Dust)	NA	NA	Varies	15 mg/m <sup>3</sup> (Total Dust)	10 mg/m <sup>3</sup> (Total Dust)
Copper Foil (Dust)	7440-50-8	231-159-6	Varies	1 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>

#### 4. FIRST-AID MEASURES

INHALATION:	Remove to fresh air. Obtain medical attention if symptoms persist.
EYE CONTACT:	Flush eyes with large amounts of water for 15 to 20 minutes. Obtain medical attention if symptoms persist.
SKIN CONTACT:	Immediately take off all contaminated clothing and flush area with water for 15 to 20 minutes. Obtain medical attention if symptoms persist.
INGESTION:	NA

#### 5. FIRE-FIGHTING MEASURES

FLASH POINT:	NE °C (°F)	Flammable Limits:	LEL	NA	UEL	NA
AUTOIGNITION TEMPERATURE:	NE °C (°F)					
EXTINGUISHING MEDIA:	<u> X </u> Water Spray	<u> X </u> Foam	<u> X </u> CO <sub>2</sub>	<u> X </u> Dry Chemical	<u> X </u> Other –	
SPECIAL FIRE FIGHTING PROCEDURES:	Decomposition in a fire may produce toxic fumes. Firefighters should be equipped with self-contained breathing apparatus and turnout gear.					
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None known.					

#### 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:	In case of fire, toxic fumes are emitted. Wear suitable protective equipment. Do not breathe dust. Eliminate sources of ignition. Avoid contact with skin and eyes.
ENVIRONMENTAL PRECAUTIONS:	Prevent from entering sewer system, surface water, or soil.
CLEANING METHODS:	Sweep or shovel into appropriate container for disposal. Avoid creation of nuisance dust.

#### 7. HANDLING AND STORAGE

HANDLING:	Wear suitable protective equipment, refer to Section 8.
STORAGE:	Keep in a cool, well-ventilated area.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:	None needed under normal conditions. If material is heated and odors are noticeable and/or irritating a respirator, meeting NIOSH requirements, should be used. A qualified individual should evaluate each situation.
<u>VENTILATION</u>	
LOCAL:	Recommended for all industrial operations.
GENERAL:	Recommended for all industrial operations.
<u>PERSONAL PROTECTION</u>	
HAND:	Gloves to avoid skin contact if desired.
EYE:	Safety glasses with side-shields are recommended in all industrial operations
SKIN:	None Required
OTHER:	Safety shower/eyewash in the area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Sheet or board (various colors); may be clad with copper.
ODOR:	None
PHYSICAL STATE:	Solid
BOILING POINT:	NA °C (°F)
MELTING POINT:	327 °C (°F)
FREEZING POINT:	NA °C (°F)
FLASH POINT:	NE °C (°F)
WATER SOLUBILITY:	In-Soluble
VAPOR DENSITY:	NA
VAPOR PRESSURE:	NA
SPECIFIC GRAVITY:	NA (Water = 1)
PARTITION COEFFICIENT:	NA
EVAPORATION RATE:	NA
RELATIVE DENSITY:	NA
VISCOSITY:	NA
AUTO-IGNITION TEMPERATURE:	NA °C (°F)
DECOMPOSITION TEMPERATURE:	NA °C (°F)
PH:	NA
FLAMMABILITY:	NA

## 10. STABILITY AND REACTIVITY

STABLE <u>X</u> UNSTABLE _____	
CONDITIONS TO AVOID:	PTFE begins to decompose above 500°F and increases rapidly above 750°F. Processing at these temperatures for prolonged periods of time is not recommended.
MATERIALS TO AVOID:	NE
HAZARDOUS POLYMERIZATION:	_____ May Occur <u>X</u> Does Not Occur
HAZARDOUS DECOMPOSITION PRODUCTS:	Decomposition may emit hydrofluoric acid, tetrafluoroethylene, hexafluoropropylene, perfluoroisobutylene, and carbonyl fluoride.

## 11. TOXICOLOGICAL INFORMATION

CARCINOGENIC STATUS:	Fiberglass (continuous filament): IARC Group 3 (unclassifiable as to carcinogenicity to humans).
ACUTE/CHRONIC:	NE
REPRODUCTIVE HAZARDS:	NE

## 12. ECOLOGICAL INFORMATION

ECOTOXICITY: NE

## 13. DISPOSAL CONSIDERATION

PHYSICAL/CHEMICAL PROPERTIES AFFECTING DISPOSAL: None  
ENVIRONMENTAL TOXICITY DATA: NE  
WASTE DISPOSAL METHOD: Dispose of in accordance with applicable federal, state, provincial, and local laws and regulations.

## 14. TRANSPORT INFORMATION

UN NUMBER: Not Regulated  
UN PROPER SHIPPING NAME: Not Regulated  
HAZARD CLASS (ES): Not Regulated  
PACKING GROUP: Not Regulated  
ENVIRONMENTAL HAZARDS: NE

## 15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS:  
Canadian (DSL/NDSL): Article - exempt  
Australian (ACIS): Article - exempt  
Korea (KECI): Article - exempt  
Japan (ENCS, MITI): Article - exempt  
China (IECSC): Article - exempt  
TSCA (Toxic Substances Control Act): All materials are listed or exempt from TSCA listing.  
CERCLA (Comprehensive Emergency Response, Compensation, and Liability Act): NA  
SARA TITLE III (Superfund Amendments and Reauthorization Act): NA  
311/312 HAZARD CATEGORIES: None

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CAS #  
7440-50-4

CHEMICAL NAME  
Copper

PERCENT BY WEIGHT  
Varies

## 16. OTHER INFORMATION

NA = Not Applicable  
NE = Not Established  
NC = Not Classified

FILE: 99411-RO1200 Series-09032020

PREPARED BY: EHS Engineering

REVIEWED BY: Corporate EHS

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF.

ROGERS CORPORATION ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.