

Standard Thickness Tolerances and Roll Length

NOMINAL THICKNESS	TOLERANCE	STANDARD ROLL LENGTH
mm (inches)	mm (inches)	m (lf)
0.79 (0.031)	± 0.127 (± 0.005)	13.3 (40)
1.60 (0.063)	± 0.165 (± 0.007)	13.3 (40)
2.39 (0.094)	± 0.254 (± 0.010)	13.3 (40)
3.18 (0.125)	± 0.432 (± 0.017)	13.3 (40)
4.78 (0.188)	± 0.560 (± 0.022)	9.1 (30)
6.35 (0.250)	± 0.560 (± 0.022)	9.1 (30)

Slit Material and Tape (PSA) Width Tolerances

NOMINAL WIDTH	TOLERANCE
mm (inches)	mm (inches)
> 0 - 76 (> 0 - 3)	± 1.60 (± 0.063)
> 76 - 203 (> 3 - 8)	± 2.39 (± 0.094)
> 203 - 305 (> 8 - 12)	± 3.18 (± 0.125)
> 305 - 610 (> 12 - 24)	± 4.78 (± 0.188)
> 610 - 914 (> 24 - 36)	+ 25.4/- 0 (+ 1/- 0)

VALUE ADDED OFFERINGS

- Acrylic Adhesive (PSA) lamination - nonconductive

- All metric conversions are approximate. Reference US customary units for official values and tolerances.
- Additional technical information is available.
- Values should not be used for specification limits.