

DeWAL® DW204-10

DeWAL® DW204-10 is produced from skived PTFE and coated with a high temperature silicone adhesive.

Features & Benefits

- Non-stick surface, low friction
- High temperature resistance
- Good insulation

Applications:

- Coil wraps
- Separators
- Transformers
- Slot liners
- Harness wrapping
- Other electrical and mechanical applications

PROPERTY	TEST METHOD	DATA RANGE	TYPICAL VALUE*
PHYSICAL			
Backing Material		---	PTFE Film
Backing Thickness, mm (inches)		0.241 - 0.267 (0.0095 - 0.0105)	---
Adhesive System		---	Silicone
Adhesive Thickness, mm (inches)		0.030 - 0.046 (0.0012 - 0.0018)	---
Adhesion, g/cm (oz./in)	ASTM-D1000	480 - 625 (43 - 56)	569 (51)
Tensile Strength, MPa (psi)	ASTM-D3759	38 - 53 (5,454 - 7,644)	47 (6,848)
Elongation, %	ASTM-D3759	269 - 445	359
Dielectric Strength, Volts/mil	ASTM-D149	1,810 - 2,684	2,091
Maximum Operating Temperature, C° (F°)			260 (500)
PRODUCT DIMENSIONS		METRIC	ENGLISH
Width mm, inches		12.7 - 546.1	0.5 - 21.5
Core Diameter mm, inches		76	3
Roll Length m, yards		33	36

*Typical values shown are from testing at date of manufacture and should not be used for specification limits.

- Additional technical information and product specifications are available upon request.

- All metric conversions are approximate.