

## DeWAL® DW 132

Pressure sensitive tape produced from PTFE impregnated glass fabric.

Suitable for covering food preparation tables, heat sealing bars, and conveyor belts.

- Smooth anti-stick surface
- Strength and dimensional stability
- Non-adhesive

PROPERTY	TEST METHOD	132-3	132-5	132-6	132-10
<b>PHYSICAL</b>					
Backing Material		PTFE Glass Cloth	PTFE Glass Cloth	PTFE Glass Cloth	PTFE Glass Cloth
Backing Thickness, inches, (mm)	ASTM-D374	0.003 (0.080)	0.005 (0.13)	0.006 (0.15)	0.010 (0.25)
Tensile Strength, lb/in, (g/cm)	ASTM-D902	70 (12500)	120 (21430)	120 (21430)	70 (12500)
Elongation, %	ASTM-D3759	5	8	8.5	5
Maximum Operating Temperature, °F, (°C)		500(260)	500 (260)	500 (260)	500 (260)
PTFE Impregnation, lb/sq yd		0.23 - 0.31	0.435 - 0.535	0.55 - 0.65	0.95 – 1.07
<b>PACKING SPECIFICATIONS</b>					
Maximum Width, inches, (mm)		40 (1016)	40 (1016)	40 (1016)	40 (1016)
Core Diameter, inches, (mm)		3 (76.2)	3 (76.2)	3 (76.2)	3 (76.2)
Roll Length, yards, (m)		36 (32.92)	36 (32.92)	36 (32.92)	36 (32.92)

All metric conversions are approximate.

Additional technical information is available.

Typical values should not be used for specification limits.